



**COMPLIANCE  
TRAINING ONLINE**

**Cal/OSHA, DOT HAZMAT, EEOC,  
EPA, HAZWOPER, HIPAA, IATA,  
IMDG, TDG, MSHA, OSHA, and  
Canada OHS Regulations and  
Safety Online Training**

**Since 2008**

This document is provided as a training aid  
and may not reflect current laws and regulations.

Be sure and consult with the appropriate governing agencies  
or publication providers listed in the "Resources" section of our website.

[www.ComplianceTrainingOnline.com](http://www.ComplianceTrainingOnline.com)



[Facebook](#)



[LinkedIn](#)



[Twitter](#)



[Website](#)



## **Aerial Lifts Protect Yourself**

Aerial lifts are vehicle-mounted, boom-supported aerial platforms, such as cherry pickers or bucket trucks, used to access utility lines and other above ground job-sites. The major causes of fatalities are falls, electrocutions, and collapses or tip overs. Employers must take measures to ensure the safe use of aerial lifts by their workers if they are required to use this equipment in the course of their employment.

### **Safe Work Practices**

- Make sure that workers who operate aerial lifts are properly trained in the safe use of the equipment.
- Maintain and operate elevating work platforms according to the manufacturer's instructions.
- Never override hydraulic, mechanical, or electrical safety devices.
- Never move the equipment with workers in an elevated platform unless this is permitted by the manufacturer.
- Do not allow workers to position themselves between overhead hazards, such as joists and beams, and the rails of the basket. Movement of the lift could crush the worker(s).
- Maintain a minimum clearance of at least 10 feet, or 3 meters, away from the nearest energized overhead lines.
- Always treat power lines, wires and other conductors as energized, even if they are down or appear to be insulated.
- Use a body harness or restraining belt with a lanyard attached to the boom or basket to prevent the worker(s) from being ejected or pulled from the basket.
- Set the brakes and use wheel chocks when on an incline.
- Use outriggers, if provided.
- Do not exceed the load limits of the equipment. Allow for the combined weight of the worker, tools and materials.

#### **For more information:**



Occupational  
Safety and Health  
Administration

U.S. Department of Labor

[www.osha.gov](http://www.osha.gov) (800) 321-OSHA (6742)

OSHA 3267-09R-11