



COMPLIANCE TRAINING
ONLINE.com

Cal/OSHA, DOT HAZMAT, EEOC, EPA, HIPAA, IATA, IMDG, TDG, MSHA, OSHA, Australia WHS, and Canada OHS Regulations and Safety Online Training

This document is provided as a training aid
and may not reflect current laws and regulations.

Be sure and consult with the appropriate governing agencies
or publication providers listed in the "Resources" section of our website.

www.ComplianceTrainingOnline.com



[Facebook](#)



[LinkedIn](#)



[Twitter](#)



[Google Plus](#)




[Website](#)

PROP 2013: TOPIC3

Focus On Roof Bolter Safety:

“Proper ATRS roof contact is important”



Preventive Roof/Rib Outreach Program

*AN ATRS SYSTEM
LOAD CAPACITY
ASSUMES
CONTACT WITH
THE MINE
ROOF— IT IS NOT
DESIGNED FOR
ANY TYPE OF
IMPACT LOAD*



- **Make sure the ATRS is set firmly against the roof:**
After the ATRS contacts the roof hold the ATRS lever for an additional 5 seconds
- **Watch for system bleed-off:**
Get hydraulic leaks fixed
Make sure check valves are functional
- **Plan for high areas like belt drives and overcasts:**
Utilize ATRS extensions
- **Make sure the ATRS pads are properly positioned:**
No more than 5 feet between pads and no more than 5 feet from the rib

