



COMPLIANCE TRAINING
ONLINE.com

Cal/OSHA, DOT HAZMAT, EEOC, EPA, HIPAA, IATA, IMDG, TDG, MSHA, OSHA, Australia WHS, and Canada OHS Regulations and Safety Online Training

This document is provided as a training aid
and may not reflect current laws and regulations.

Be sure and consult with the appropriate governing agencies
or publication providers listed in the "Resources" section of our website.

www.ComplianceTrainingOnline.com



[Facebook](#)



[LinkedIn](#)



[Twitter](#)



[Google Plus](#)



[Website](#)



Right to Know Hazardous Substance Fact Sheet

Common Name: **BENZENE**

Synonyms: Benzin; Benzol; Phenyl Hydride

Chemical Name: Benzene

Date: October 2008 Revision: July 2015

CAS Number: 71-43-2

RTK Substance Number: 0197

DOT Number: UN 1114

Description and Use

Benzene is a clear, colorless liquid with a sweet *Petroleum*-like odor. It is used as a solvent and in making plastics, resins, dyes and pesticides. It is also found in *Gasoline*.

- ▶ **ODOR THRESHOLD= 12 ppm**
- ▶ Odor thresholds vary greatly. Do not rely on odor alone to determine potentially hazardous exposures.

Reasons for Citation

- ▶ **Benzene** is on the Right to Know Hazardous Substance List because it is cited by OSHA, ACGIH, DOT, NIOSH, NTP, DEP, IARC, NFPA and EPA.
- ▶ This chemical is on the Special Health Hazard Substance List.

SEE GLOSSARY ON PAGE 5.

FIRST AID

Eye Contact

- ▶ Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while rinsing.

Skin Contact

- ▶ Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of soap and water.

Inhalation

- ▶ Remove the person from exposure
- ▶ Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ▶ Transfer promptly to a medical facility.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

EMERGENCY RESPONDERS >>>> SEE BACK PAGE

Hazard Summary

Hazard Rating	NJDHSS	NFPA
HEALTH	4	2
FLAMMABILITY	-	3
REACTIVITY	-	0
CARCINOGEN FLAMMABLE POISONOUS GASES ARE PRODUCED IN FIRE CONTAINERS MAY EXPLODE IN FIRE		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ▶ **Benzene** can affect you when inhaled and by passing through the skin.
- ▶ **Benzene** is a CARCINOGEN and MUTAGEN. HANDLE WITH EXTREME CAUTION.
- ▶ **Benzene** can irritate the skin and eyes with drying and scaling of the skin.
- ▶ Inhaling **Benzene** can irritate the nose and throat.
- ▶ **Benzene** can cause headache, dizziness, nausea and vomiting. Convulsions and coma, or sudden death from irregular heartbeat, may follow high exposure.
- ▶ Repeated exposure can cause damage to the blood cells (aplastic anemia).
- ▶ **Benzene** is a FLAMMABLE LIQUID and a DANGEROUS FIRE HAZARD.

Workplace Exposure Limits

OSHA: The legal airborne permissible exposure limit (PEL) is **1 ppm** averaged over an 8-hour workshift and **5 ppm**, not to be exceeded during any 15-minute work period.

NIOSH: The recommended airborne exposure limit (REL) is **0.1 ppm** averaged over a 10-hour workshift and **1 ppm**, not to be exceeded during any 15-minute work period.

ACGIH: The threshold limit value (TLV) is **0.5 ppm** averaged over an 8-hour workshift and **2.5 ppm** as a STEL (short-term exposure limit).

- ▶ **Benzene** is a CARCINOGEN in humans. There may be no safe level of exposure to a carcinogen, so all contact should be reduced to the lowest possible level.
- ▶ The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.